

HANNA Testers

pH • EC • TDS • ORP • Temperature



Features

- Dual-level LCDs
- Automatic Shut-off
- Efficient 2-button Operation
- Temperature in °C or °F
- Close Proximity Temperature Probes
- Automatic Calibration (most models)
- Battery Error Prevention Systems (BEPS)
- Automatic Temperature Compensation (most models)

Waterproof
&
Floating

The World's Most Advanced Line Of Testers

With these powerful waterproof testers, you can easily measure pH, EC/TDS, temperature, and now ORP, anywhere. Attention to detail is evident in these advanced instruments with features such as replaceable electrode technology and stainless steel temperature probes for faster, more precise measurements. The EC/TDS meters have graphite probes for fast response and contamination resistance.



Replaceable Electrodes

The stainless steel round connector of the electrode means there are no pins no bend or break during replacement.

Rejuvenating pH Junctions

The pH replaceable electrode features a pull-out cloth junction. When the cloth junction becomes dirty from testing, simply pull out 3 mm (1/8") to rejuvenate the electrode.

Contamination Resistant Conductivity Electrode

HANNA's graphite conductivity electrode resists contamination from salt deposits in the solution.

HANNA Testers



| SPECIFICATIONS | pHep®4 | pHep®5 | DIST®5 | DIST®6 | ORP | pH/ORP Combo | pH/EC Combo | pH/EC Combo |
|--|---|----------|----------|----------|----------|--------------|-------------|-------------|
| Model Number | HI 98127 | HI 98128 | HI 98311 | HI 98312 | HI 98120 | HI 98121 | HI 98129 | HI 98130 |
| Range | pH -2.0 to 16.0 | • | | | | | | |
| | pH -2.00 to 16.00 | | • | | | • | | |
| | pH 0.00 to 14.00 | | | | | | • | • |
| | EC 0 to 3999 μ S/cm | | • | | | | • | |
| | EC 0.00 to 20.00 mS/cm | | | • | | | | • |
| | TDS 0 to 2000 ppm | | • | | | | • | |
| | TDS 0.00 to 10.00 ppt | | | • | | | | • |
| | ORP \pm 1000 mV | | | | • | • | | |
| | Temperature 0.0 to 60.0 °C | • | • | • | • | • | • | • |
| | Temperature 32.0 to 140.0 °F | • | • | • | • | • | • | • |
| Resolution | 0.1 pH | • | | | | | | |
| | 0.01 pH | | • | | | • | • | • |
| | 1 μ S/cm EC | | • | | | | • | |
| | 0.01 mS/cm EC | | | • | | | | • |
| | 1 ppm TDS | | • | | | | • | |
| | 0.01 ppt TDS | | | • | | | | • |
| | 1 mV ORP | | | | • | • | | |
| | 0.1°F/°C | • | • | • | • | • | • | • |
| Accuracy (@20°C/68°F) | \pm 0.1 pH | • | | | | | | |
| | \pm 0.05 pH | | • | | | • | • | • |
| | \pm 2% F.S. EC/TDS | | • | • | | | • | • |
| | \pm 2 mV ORP | | | | • | • | | |
| | \pm 0.5 °C | • | • | • | • | • | • | • |
| | \pm 1 °F | • | • | • | • | • | • | • |
| Calibration* | pH Automatic* | • | • | | | • | • | • |
| | EC/TDS Automatic** | | | • | • | | • | • |
| Automatic Temperature Compensation | | • | • | • | | • | • | • |
| Battery Type | (4) 1.5V | • | • | • | • | • | • | • |
| Battery Life (hours) | 300 | 300 | 100 | 100 | 300 | 250 | 100 | 100 |
| Battery Error Prevention System (BEPS) | • | • | • | • | • | • | • | • |
| Auto-off after 8 minutes | • | • | • | • | • | • | • | • |
| Dimensions/Weight | 163 x 40 x 26 mm(6.4 x 1.6 x 1")/85 g (3.0 oz.) | | | | | | | |

*1 or 2 points with 2 sets of memorized buffers, (pH 4.01/ 7.01/10.01 or pH 4.01/6.86/9.18)

**1 point at 1413 μ S/cm or 12.88 mS/cm

ACCESSORIES

| | | | | | |
|------------------|--|------------------|---|------------------|--|
| HI 7061M | Electrode cleaning solution, 230 mL bottle | HI 7021M | ORP test solution (240 mV), 230 mL bottle | HI 70442P | 1500 ppm @ 25 °C calibration solution, 20 mL sachet (25 pcs) |
| HI 70004P | pH 4.01 solution, 20 mL sachet (25 pcs) | HI 7022M | ORP test solution (470 mV), 230 mL bottle | HI 70300M | Electrode storage solution, 230 mL bottle |
| HI 70006P | pH 6.86 solution, 20 mL sachet (25 pcs) | HI 7091M | Pretreatment reducing sol., 230 mL bottle | HI 73128 | Electrode removal tool |
| HI 70007P | pH 7.01 solution, 20 mL sachet (25 pcs) | HI 7092M | Pretreatment oxidizing sol., 230 mL bottle | | |
| HI 70009P | pH 9.18 solution, 20 mL sachet (25 pcs) | HI 70030P | 12.88 mS/cm @ 25 °C calibration solution, 20 mL sachet (25 pcs) | | |
| HI 70010P | pH 10.01 solution, 20 mL sachet (25 pcs) | HI 70031P | 1413 μ S/cm @ 25 °C calibration solution, 20 mL sachet (25 pcs) | | |
| HI 70006P | pH 6.86 solution, 20 mL sachet (25 pcs) | HI 70032P | 1382 ppm @ 25 °C calibration solution, 20 mL sachet (25 pcs) | | |
| HI 7004M | pH 4.01 solution, 230 mL bottle | HI 70038P | 6.44 ppt @ 25 °C calibration solution, 20 mL sachet (25 pcs) | | |
| HI 7006M | pH 6.86 solution, 230 mL bottle | | | | |
| HI 7007M | pH 7.01 solution, 230 mL bottle | | | | |
| HI 7009M | pH 9.18 solution, 230 mL bottle | | | | |
| HI 7010M | pH 10.01 solution, 230 mL bottle | | | | |

ORDERING INFORMATION

All Testers are supplied with cap, electrode removal tool, (4) 1.5V batteries and instruction manual.