

Creation Date 01-Feb-2010

Revision Date 16-Sep-2021

Revision Number 11

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Description: Formaldehyde solution 37-41%
Cat No. : F/1501/PB08, F/1501/PB15, F/1501/PB17, F/1501/25, F/1501/99
Synonyms Formalin; Formol; Methanal
Molecular Formula C H₂ O

Unique Formula Identifier (UFI) F5US-FQ5M-VS2M-YVU4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.
Uses advised against No Information available

1.3. Details of the supplier of the safety data sheet

Company **UK entity/business name**
 Fisher Scientific UK
 Bishop Meadow Road, Loughborough,
 Leicestershire LE11 5RG, United Kingdom

EU entity/business name
 Acros Organics BVBA
 Janssen Pharmaceuticaaan 3a
 2440 Geel, Belgium

E-mail address begel.sdsdesk@thermofisher.com

1.4. Emergency telephone number

Tel: 01509 231166
 Chemtrec US: (800) 424-9300
 Chemtrec EU: 001 (202) 483-7616

Poison Centre - Emergency information services **Ireland** : National Poisons Information Centre (NPIC) - **01 809 2166** (8am-10pm, 7 days a week)
Malta : +356 2395 2000
Cyprus : +357 2240 5611

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

CLP Classification - Regulation (EC) No 1272/2008

Physical hazards

Flammable liquids

Category 3 (H226)

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Health hazards

Acute oral toxicity	Category 3 (H301)
Acute dermal toxicity	Category 3 (H311)
Acute Inhalation Toxicity - Vapors	Category 3 (H331)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Skin Sensitization	Category 1 (H317)
Germ Cell Mutagenicity	Category 2 (H341)
Carcinogenicity	Category 1B (H350)
Specific target organ toxicity - (single exposure)	Category 1 (H370)
	Category 3 (H335)

Environmental hazards

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

2.2. Label elements



Signal Word

Danger

Hazard Statements

- H226 - Flammable liquid and vapor
- H301 + H311 + H331 - Toxic if swallowed, in contact with skin or if inhaled
- H314 - Causes severe skin burns and eye damage
- H317 - May cause an allergic skin reaction
- H335 - May cause respiratory irritation
- H341 - Suspected of causing genetic defects
- H350 - May cause cancer
- H370 - Causes damage to organs

Precautionary Statements

- P202 - Do not handle until all safety precautions have been read and understood
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301 + P330 + P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting
- P302 + P352 - IF ON SKIN: Wash with plenty of soap and water
- P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Additional EU labelling

Restricted to professional users

2.3. Other hazards

Lachrymator (substance which increases the flow of tears)

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Component	CAS No	EC No	Weight %	CLP Classification - Regulation (EC) No 1272/2008
Formaldehyde	50-00-0	200-001-8	35-41	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) Muta. 2 (H341) STOT SE 3 (H335)
Methyl alcohol	67-56-1	200-659-6	5-15	Flam. Liq. 2 (H225) Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370)
Water	7732-18-5	231-791-2	40-46	-

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Formaldehyde	Skin Corr. 1B :: C>=25% Eye Irrit. 2 :: 5%<=C<25% Skin Irrit. 2 :: 5%<=C<25% Skin Sens. 1 :: C>=0.2% STOT SE 3 :: C>=5%	-	-
Methyl alcohol	STOT SE 1 (H370) :: C>=10% STOT SE 2 (H371) :: 3%<=C<10%	-	-

Components	Reach Registration Number
Methanol	01-2119433307-44
Formaldehyde	01-2119488953-20

Full text of Hazard Statements: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General Advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Immediate medical attention is required.
Ingestion	Do NOT induce vomiting. Call a physician or poison control center immediately.
Inhalation	If breathing is difficult, give oxygen. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Remove to fresh air. Immediate medical attention is required.

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Self-Protection of the First Aider Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. May cause allergic skin reaction. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically. Symptoms may be delayed.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Water spray, carbon dioxide (CO₂), dry chemical, alcohol-resistant foam. Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Formic acid, Oxygen from the air can oxidize formaldehyde to formic acid, especially when heated, Carbon monoxide (CO), Carbon dioxide (CO₂).

5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.

6.2. Environmental precautions

Should not be released into the environment. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

spark-proof tools and explosion-proof equipment.

6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Do not ingest. If swallowed then seek immediate medical assistance. Do not breathe mist/vapors/spray. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. Take precautionary measures against static discharges.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Corrosives area. Keep away from heat, sparks and flame.

Technical Rules for Hazardous Substances (TRGS) 510 Storage Class (LGK)
(Germany)

Class 3

7.3. Specific end use(s)

Use in laboratories

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Third edition. Published 2018. **IRE** - 2018 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Formaldehyde	STEL: 2 ppm 15 min STEL: 2.5 mg/m ³ 15 min TWA: 2 ppm 8 hr TWA: 2.5 mg/m ³ 8 hr Carc.	TWA: 0.37 mg/m ³ (8h) TWA: 0.3 ppm (8h) Skin STEL: 0.74 mg/m ³ (8h) STEL: 0.6 ppm (8h)	TWA: 0.3 ppm 8 hr. TWA: 0.5 ppm 8 hr. for the healthcare, funeral and embalming sectors until July 11, 2024 TWA: 0.37 mg/m ³ 8 hr. TWA: 0.62 mg/m ³ 8 hr. for the healthcare, funeral and embalming sectors until July 11, 2024 STEL: 0.6 ppm 15 min STEL: 0.738 mg/m ³ 15 min STEL: 0.62 mg/m ³ 15 min
Methyl alcohol	WEL - TWA: 200 ppm TWA; 266 mg/m ³ TWA WEL - STEL: 250 ppm STEL; 333 mg/m ³ STEL	TWA: 200 ppm 8 hr TWA: 260 mg/m ³ 8 hr Skin	TWA: 200 ppm 8 hr. TWA: 260 mg/m ³ 8 hr. STEL: 600 ppm 15 min STEL: 780 mg/m ³ 15 min Skin

Biological limit values

List source(s):

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Formaldehyde 50-00-0 (35-41)			DNEL = 37µg/cm ²	DNEL = 240mg/kg bw/day
Methyl alcohol 67-56-1 (5-15)		DNEL = 20mg/kg bw/day		DNEL = 20mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Formaldehyde 50-00-0 (35-41)	DNEL = 0.75mg/m ³		DNEL = 0.375mg/m ³	DNEL = 9mg/m ³
Methyl alcohol 67-56-1 (5-15)	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³	DNEL = 130mg/m ³

Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Formaldehyde 50-00-0 (35-41)	PNEC = 0.44mg/L	PNEC = 2.3mg/kg sediment dw	PNEC = 4.44mg/L	PNEC = 0.19mg/L	PNEC = 0.2mg/kg soil dw
Methyl alcohol 67-56-1 (5-15)	PNEC = 20.8mg/L	PNEC = 77mg/kg sediment dw	PNEC = 1540mg/L	PNEC = 100mg/L	PNEC = 100mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Formaldehyde 50-00-0 (35-41)	PNEC = 0.44mg/L	PNEC = 2.3mg/kg sediment dw			
Methyl alcohol 67-56-1 (5-15)	PNEC = 2.08mg/L	PNEC = 7.7mg/kg sediment dw			

8.2. Exposure controls

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Goggles (European standard - EN 166)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Viton (R)	> 480 minutes	0.7 mm	EN 374	As tested under EN374-3 Determination of Resistance to Permeation by Chemicals
Nitrile rubber	> 360 minutes	15 - 22 mil		
Butyl rubber	> 240 minutes	25 -35 mil		
Neoprene gloves	> 60 minutes	18 - 24 mil		

Skin and body protection Long sleeved clothing.

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Recommended half mask:- Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical State	Liquid	
Appearance	Colorless	
Odor	Irritating pungent	
Odor Threshold	0.8 - 1 ppm	
Melting Point/Range	-15 °C / 5 °F	
Softening Point	No data available	
Boiling Point/Range	97 °C / 206.6 °F	@ 760 mmHg
Flammability (liquid)	Flammable	On basis of test data
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	Lower 7 vol% Upper 73 vol%	
Flash Point	50 °C / 122 °F	Method - No information available
Autoignition Temperature	424 °C / 795.2 °F	
Decomposition Temperature	> 150°C	
pH	3-4.2	
Viscosity	1.0 mPas @ 20°C	
Water Solubility	Miscible	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Formaldehyde	-0.35	
Methyl alcohol	-0.74	
Vapor Pressure	2 mbar @ 20 °C	
Density / Specific Gravity	1.083	
Bulk Density	Not applicable	Liquid
Vapor Density	> 1.0	(Air = 1.0)
Particle characteristics	Not applicable (liquid)	

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

9.2. Other information

Molecular Formula	C H ₂ O
Molecular Weight	30.02
Explosive Properties	explosive air/vapour mixtures possible

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None known, based on information available

10.2. Chemical stability

Stable under normal conditions. Stabilized with Methanol. Hazardous polymerization may occur upon depletion of inhibitor.

10.3. Possibility of hazardous reactions

Hazardous Polymerization Hazardous Reactions

Hazardous polymerization may occur upon depletion of inhibitor. Reaction of formaldehyde with nitrogen dioxide, nitromethane, perchloric acid and aniline, or peroxyformic acid yields explosive compounds. Formaldehyde reacts with hydrochloric acid to form the potent carcinogen bis-chloromethyl ether. The substance can react dangerously with: strong oxidizing agents, potassium permanganate, magnesium carbonate, sodium hydroxide, perchloric acid + aniline, hydrochloric acid. The substance polymerize in contact with: alkali, nitrides, polymerization initiators. Risk of explosion in contact with: nitric acid, hydrogen peroxide, nitromethane, performic acid, peracetic acid, phenol, nitrogen dioxide (180 °C). Exothermic reaction with: bases, nitrides, polymerisation initiators, Sodium hydroxide, potassium permanganate, furfuryl alcohol, strong oxidizing agent.

10.4. Conditions to avoid

Temperatures above 65°C. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Potassium permanganate. Peroxides. Perchloric acid + aniline. Strong bases. Sodium hydroxide. Ammonia. Hydroxides. Sodium bisulfite. Strong acids. Hydrogen chloride. Isocyanates. Acid anhydrides. Magnesium carbonates. Iodine.

10.6. Hazardous decomposition products

Formic acid. Oxygen from the air can oxidize formaldehyde to formic acid, especially when heated. Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Product Information

(a) acute toxicity;

Oral	Category 3 ATE = 192 mg/kg
Dermal	Category 3 ATE = 495 mg/kg
Inhalation	Category 3 ATE = 1.3 mg/l

Toxicology data for the components

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Formaldehyde	500 mg/kg (Rat)	LD50 = 270 mg/kg (Rabbit)	0.578 mg/L (Rat) 4 h
Methyl alcohol	LD50 = 1187 – 2769 mg/kg (Rat)	LD50 = 17100 mg/kg (Rabbit)	LC50 = 128.2 mg/L (Rat) 4 h
Water	-	-	-

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

(d) respiratory or skin sensitization;

Respiratory No data available
Skin Category 1

Component	Test method	Test species	Study result
Formaldehyde 50-00-0 (35-41)	Skin sensitization Test method Patch Test Respiratory sensitization in vitro	Man guinea pig	Sensitizer Sensitization
Methyl alcohol 67-56-1 (5-15)	OECD Test Guideline 406 Guinea Pig Maximisation Test (GPMT)	guinea pig	non-sensitising

May cause sensitization by skin contact

(e) germ cell mutagenicity; Category 2

Mutagenic effects have occurred in humans

(f) carcinogenicity; Category 1B

The table below indicates whether each agency has listed any ingredient as a carcinogen

Component	EU	UK	Germany	IARC
Formaldehyde	Carc Cat. 1B	Cat 3		Group 1

(g) reproductive toxicity; No data available

Component	Test method	Test species / Duration	Study result
Methyl alcohol 67-56-1 (5-15)	OECD Test Guideline 416	Rat / Inhalation 2 Generation	NOAEC = 1.3 mg/l (air)

Developmental Effects Component substance is listed on California Proposition 65 as a developmental hazard.

(h) STOT-single exposure; Category 1

Results / Target organs Respiratory system, Optic nerve, Central nervous system (CNS).

(i) STOT-repeated exposure; No data available

Target Organs No information available.

(j) aspiration hazard; No data available

Symptoms / effects, both acute and delayed Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain or flushing. Symptoms of

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

overexposure may be headache, dizziness, tiredness, nausea and vomiting. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

11.2. Information on other hazards

Endocrine Disrupting Properties Assess endocrine disrupting properties for human health This product does not contain any known or suspected endocrine disruptors

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Contains no substances known to be hazardous to the environment or that are not degradable in waste water treatment plants.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Formaldehyde	Leuciscus idus: LC50 = 15 mg/L 96h	EC50 = 20 mg/L 96h EC50 = 2 mg/L 48h	
Methyl alcohol	Pimephales promelas: LC50 > 10000 mg/L 96h	EC50 > 10000 mg/L 24h	

Component	Microtox	M-Factor
Methyl alcohol	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	

12.2. Persistence and degradability

Not applicable for mixtures

Persistence

Soluble in water, Persistence is unlikely, based on information available.

Component	Degradability
Methyl alcohol 67-56-1 (5-15)	DT50 ~ 17.2d >94% after 20d

Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Formaldehyde	-0.35	No data available
Methyl alcohol	-0.74	<10

12.4. Mobility in soil

The product is water soluble, and may spread in water systems . Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

12.5. Results of PBT and vPvB assessment

No data available for assessment.

12.6. Endocrine disrupting properties

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

12.7. Other adverse effects

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

SECTION 13: DISPOSAL CONSIDERATIONS

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

13.1. Waste treatment methods

Waste from Residues/Unused Products	Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.
Contaminated Packaging	Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.
European Waste Catalogue (EWC)	According to the European Waste Catalog, Waste Codes are not product specific, but application specific.
Other Information	Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

SECTION 14: TRANSPORT INFORMATION

IMDG/IMO

14.1. UN number	UN1198
14.2. UN proper shipping name	FORMALDEHYDE SOLUTION, FLAMMABLE
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	III

ADR

14.1. UN number	UN1198
14.2. UN proper shipping name	FORMALDEHYDE SOLUTION, FLAMMABLE
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	III

IATA

14.1. UN number	UN1198
14.2. UN proper shipping name	FORMALDEHYDE SOLUTION, FLAMMABLE
14.3. Transport hazard class(es)	3
Subsidiary Hazard Class	8
14.4. Packing group	III

14.5. Environmental hazards	No hazards identified
14.6. Special precautions for user	No special precautions required
14.7. Maritime transport in bulk according to IMO instruments	Not applicable, packaged goods

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

International Inventories

X = listed, Europe (EINECS/ELINCS/NLP), U.S.A. (TSCA), Canada (DSL/NDSL), Philippines (PICCS), China (IECSC), Japan (ENCS), Japan (ISHL), Australia (AICS), Korea (KECL).

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Component	EINECS	ELINCS	NLP	TSCA	DSL	NDSL	PICCS	IECSC	ENCS	ISHL	AICS	KECL
Formaldehyde	200-001-8	-		X	X	-	X	X	X	X	X	KE-17074
Methyl alcohol	200-659-6	-		X	X	-	X	X	X	X	X	KE-23193
Water	231-791-2	-		X	X	-	X	X	X		X	KE-35400

Component	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Formaldehyde		Use restricted. See item 72. (see link for restriction details) Use restricted. See item 28. (see link for restriction details) Use restricted. See item 75. (see link for restriction details)	
Methyl alcohol		Use restricted. See item 69. (see link for restriction details)	

<https://echa.europa.eu/substances-restricted-under-reach>

Component	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Formaldehyde	5 tonne	50 tonne
Methyl alcohol	500 tonne	5000 tonne

Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

National Regulations

WGK Classification

Water endangering class = 3 (self classification)

Component	Germany - Water Classification (VwVwS)	Germany - TA-Luft Class
Formaldehyde	WGK 3	Class I : 20 mg/m ³ (Massenkonzentration)
Methyl alcohol	WGK 2	

Component	France - INRS (Tables of occupational diseases)
Formaldehyde	Tableaux des maladies professionnelles (TMP) - RG 43
Methyl alcohol	Tableaux des maladies professionnelles (TMP) - RG 84

UK - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

Take note of Dir 76/769/EEC relating to restrictions on the marketing and use of certain dangerous substances and preparations

15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

SECTION 16: OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3

- H225 - Highly flammable liquid and vapor
- H301 - Toxic if swallowed
- H311 - Toxic in contact with skin
- H331 - Toxic if inhaled
- H314 - Causes severe skin burns and eye damage
- H317 - May cause an allergic skin reaction
- H318 - Causes serious eye damage
- H341 - Suspected of causing genetic defects
- H350 - May cause cancer
- H370 - Causes damage to organs

SAFETY DATA SHEET

Formaldehyde solution 37-41%

Revision Date 16-Sep-2021

Legend

CAS - Chemical Abstracts Service

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

IECSC - Chinese Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

ENCS - Japanese Existing and New Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

WEL - Workplace Exposure Limit

ACGIH - American Conference of Governmental Industrial Hygienists

DNEL - Derived No Effect Level

RPE - Respiratory Protective Equipment

LC50 - Lethal Concentration 50%

NOEC - No Observed Effect Concentration

PBT - Persistent, Bioaccumulative, Toxic

TWA - Time Weighted Average

IARC - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

ADR - European Agreement Concerning the International Carriage of Dangerous Goods by Road

IMO/MDG - International Maritime Organization/International Maritime Dangerous Goods Code

OECD - Organisation for Economic Co-operation and Development

BCF - Bioconcentration factor

Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

ICAO/IATA - International Civil Aviation Organization/International Air Transport Association

MARPOL - International Convention for the Prevention of Pollution from Ships

ATE - Acute Toxicity Estimate

VOC - (Volatile Organic Compound)

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards On basis of test data

Health Hazards Calculation method

Environmental hazards Calculation method

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Chemical incident response training.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Creation Date 01-Feb-2010

Revision Date 16-Sep-2021

Revision Summary Not applicable.

**This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006
COMMISSION REGULATION (EU) 2020/878 amending Annex II to Regulation (EC) No
1907/2006**

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet